KERN ALJ160-4A



160000

Analytical balance range with large weighing ranges - now also with EC type approval [M] or available as semi-micro analytical balance

Counting

Counting resolution:



Measuring system

Adjustment options:	Internal calibration (manual) External calibration Internal calibration (auto)
Linearity:	0,300 mg
Minimum weight (USP):	200 mg
Readability [d]:	0,100 mg
Recommended adjusting weight:	150 g (E2)
Repeatability:	0,100 mg
Resolution:	1.600.000
Stabilisation time under laboratory conditions:	4 s
Tare range:	160 g
Warm up time:	8 h
Weighing capacity [Max]:	160 g
Weighing system:	Force compensation
Weighing units:	ct dwt g gn lb mg mo oz ozt tl (HK) tl (Singap. Malays) tl (Tw)

Display

Display digit height:

1,700 cm

Technical data about verification

Verification class:

```
I (ohne Bauartzulassung)
```

KERN & SOHN GmbH · Ziegelei 1 · 72336 Balingen · Germany · Tel. +49-(0)7433 - 99 33-0 · www.kern-sohn.com

	100000
Mininum piece weight at piece counting (Laboratory:	1 mg
Mininum piece weight at piece counting (Normal):	10 mg
Reference weight:	yes
Functions	
Counting function:	yes
Density determination function:	yes
Peak function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Standby function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C
Power supply	
Power supply Input voltage:	country-dependent
	country-dependent Mains adapter external
Input voltage:	
Input voltage: Mains adapter:	Mains adapter external
Input voltage: Mains adapter: Mains adapter/adapter included:	Mains adapter external
Input voltage: Mains adapter: Mains adapter/adapter included: Service	Mains adapter external CH EURO UK US
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate:	Mains adapter external CH EURO UK US
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category	Mains adapter external CH EURO UK US 963-101
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category Brand:	Mains adapter external CH EURO UK US 963-101 KERN
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category Brand: Category:	Mains adapter external CH EURO UK US 963-101 KERN Balances
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category Brand: Category: Product Group:	Mains adapter external CH EURO UK US 963-101 KERN Balances
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping	Mains adapter external CH EURO UK US 963-101 KERN Balances Analytical balance
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery:	Mains adapter external CH EURO UK US 963-101 KERN Balances Analytical balance 24 h
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Mains adapter external CH EURO UK US 963-101 KERN Balances Analytical balance 24 h 515 x 400 x 630 mm
Input voltage: Mains adapter: Mains adapter/adapter included: Service DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Mains adapter external CH EURO UK US 963-101 KERN Balances Analytical balance 24 h 515 x 400 x 630 mm 9,250 kg

KERN ALJ160-4A



Analytical balance range with large weighing ranges - now also with EC type approval [M] or available as semi-micro analytical balance

Construction	
Casing material:	Plastic
Dimensions draft shield (WxDxH):	190 x 195 x 225 mm
Dimensions housing (WxDxH):	210 x 340 x 330 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing space (WxDxH):	160 x 140 x 205 mm
Weighing surface (d):	80

Piktogramme

STANDARD



OPTION

DAkkS +3 Days

FACTORY

