KERN ALJ250-4A



Analytical balance range with large weighing ranges - now also with EC type approval [M] or available as semi-micro analytical balance



Measuring system

| 3 7 | |
|---|--|
| Adjustment options: | Internal calibration (manual) External calibration Internal calibration (auto) |
| Linearity: | 0,300 mg |
| Minimum weight (USP): | 200 mg |
| Readability [d]: | 0,100 mg |
| Repeatability: | 0,100 mg |
| Resolution: | 2.500.000 |
| Stabilisation time under laboratory conditions: | 4 s |
| Tare range: | 250 g |
| Warm up time: | 8 h |
| Weighing capacity [Max]: | 250 g |
| Weighing system: | Force compensation |
| Weighing units: | ct g gn lb oz ozt tl (HK) tl (Singap. Malays) tl (Tw) |
| Display | |
| Display digit height: | 1,700 cm |

Technical data about verification

Verification class:

I (ohne Bauartzulassung)

| Counting | |
|--|------------------------|
| Counting resolution: | 250000 |
| Mininum piece weight at piece counting (Laboratory: | 1 mg |
| Mininum piece weight at piece | 10 mg |
| counting (Normal): | |
| Reference weight: | yes |
| Functions | |
| Counting function: | yes |
| Density determination function: | yes |
| Peak function: | yes |
| Percentage determination: | yes |
| PRE-TARE function: | yes |
| Standby function: | yes |
| Vibration-free weighing (Animal weighing program): | yes |
| Weighing with tolerance range: | yes |
| Environmental conditions | |
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5 °C |
| Power supply | |
| Input voltage: | country-dependent |
| Mains adapter: | Mains adapter external |
| Mains adapter/adapter included: | CH EURO UK US |
| Service | |
| DAkkS Certificate: | 963-101 |
| Category | |
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Analytical balance |
| Packaging & shipping | |
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 515 x 400 x 630 mm |
| Gross weight: | 9,600 kg |
| Net weight: | 6,500 kg |
| Shipping method: | Parcel service |
| - 11 5 | |

KERN ALJ250-4A



Analytical balance range with large weighing ranges - now also with EC type approval [M] or available as semi-micro analytical balance

| Construction | |
|-------------------------------------|--------------------|
| Casing material: | Plastic |
| Dimensions draft shield (WxDxH): | 190 x 195 x 225 mm |
| Dimensions housing (WxDxH): | 210 x 340 x 330 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 210 x 340 x 330 mm |
| Revolving screw feet: | yes |
| Weighing space (WxDxH): | 160 x 140 x 205 mm |
| Weighing surface (d): | 80 |

Piktogramme

STANDARD



OPTION

DAkks +3 days

FACTORY

