

KERN DE 150K20DXL

The long-time success story with dust and spray protected display device



Measuring system

Adjustment options:	External calibration
Linearity:	60 g 150 g
Readability [d]:	20 g 50 g
Recommended adjusting weight:	150 kg (M1)
Repeatability:	20 g 50 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2,500 s
Tare range:	150 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	60 kg 150 kg
Weighing system:	Strain gauge
Weighing units:	dwt kg lb mo oz ozt tl (HK) tl (Tw) tol

Display

Display digit height:	2,500 cm
-----------------------	----------

Counting

Counting resolution:	3750
Minimum piece weight at piece counting (Laboratory):	40 g
Minimum piece weight at piece counting (Normal):	400 g

Functions

Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Battery:	9 V Block
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time:	12 h
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional

Service

Adjustment at the location of installation: 961-249

DAkkS Certificate:	963-129
--------------------	---------

Category

Brand:	KERN
Category:	Balances
Product Group:	Platform scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	775 x 720 x 220 mm
Gross weight:	30,900 kg
Net weight:	27,700 kg
Shipping method:	Parcel service

Construction

Cable length of display device:	1,400 m
Dimensions of display device (WxDxH):	225 x 110 x 45 mm
Dimensions of weighing plate (WxDxH):	650 x 500 x 89 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	650 x 500 mm


KERN DE 150K20DXL

The long-time success story with dust and spray protected display device



Piktogramme

STANDARD



OPTION

