KERN EWJ3000-2



80 %

Plastic

yes

220 x 315 x 105 mm

1

stainless steel

High-quality precision balance with automatic internal adjustment, also with EC type approval [M]



Maximum operating temperature:	35 °C
Minimum ambient temperature:	15 °C
Power supply	
Charging time:	12 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	CH EURO UK US
Operating time (Backlight off):	20 h
Operating time (Backlight on):	10 h
Rechargeable battery:	Rchrg. battery optional - intern
Service	
DAkkS Certificate:	963-127
Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	390 x 280 x 270 mm
Gross weight:	4,120 kg
Net weight:	2,886 kg
Shipping method:	Parcel service

Environmental conditions

Maximum humidity:

Measuring system	
Adjustment options:	Internal calibration (auto)
Linearity:	50 mg
Minimum weight (USP):	40 g
Readability [d]:	10 mg
Repeatability:	20 mg
Resolution:	300000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	2 h
Weighing capacity [Max]:	3 kg
Weighing system:	Strain gauge
Weighing units:	ct dwt lb mo oz ozt tl (HK) tl (Singap. Malays) tl (Tw)
D'all	

	(5924
Display	
Display digit height:	1,650 cm
Counting	
Counting resolution:	150000
Mininum piece weight at piece counting (Laboratory:	20 mg
Mininum piece weight at piece counting (Normal):	200 mg

Functions	
Capacity display:	yes
Counting function:	yes
Percentage determination:	yes

Construction

Casing material:

Level indicator:

Material weighing plate:

Dimensions housing (WxDxH):

KERN EWJ3000-2



High-quality precision balance with automatic internal adjustment, also with EC type approval [M]

PIKTOGRAMME STANDARD GLP CAL INT RS 232 USB PRINTER PCS RECIPE PERCENT UNIT MULTI DAKKS ACCU +3 DAYS FACTORY