KERN IOC10K-4



All-round platform scale with a range of communication options and EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	10 g 25 g
Linearisation (points):	3
Linearity:	6 g 15 g
Load cell connection:	4-wire
Readability [d]:	200 mg 500 mg
Recommended adjusting weight:	15 kg (M1)
Repeatability:	2 g 5 g
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	2 h 2 h
Weighing capacity [Max]:	6 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	tJ HJ PCS oz g lb kg
Display	

Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm
Technical data about verification	
Minimum load [Min]:	40 g 100 g
Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	500 mg
Mininum piece weight at piece	5 g

Functions				
Counting function:	yes			
Percentage determination:	yes			
PRE-TARE function:	yes			
Vibration-free weighing (Animal weighing program):	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0%			
Power supply				
Battery:	no battery			
Charging time:	3 h			
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	US EURO CH UK AUS			
Operating time:	100 h			
Operating time (Backlight off):	43 h			
Operating time (Backlight on):	26 h			
Rechargeable battery:	Rchrg. battery optional			
Services (optional)				
Services (optional) Adjustment at the location of installatio	n:961-248			
Adjustment at the location of installatio				
	n:961-248 963-128			
Adjustment at the location of installatio				
Adjustment at the location of installatio DAkkS Certificate:				
Adjustment at the location of installation DAkkS Certificate: Category	963-128			
Adjustment at the location of installation DAkkS Certificate: Category Brand:	963-128 KERN			
Adjustment at the location of installatio DAkkS Certificate: Category Brand: Category:	963-128 KERN Balances			
Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group:	963-128 KERN Balances			
Adjustment at the location of installatio DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping	963-128 KERN Balances Industiral scale			
Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery:	963-128 KERN Balances Industiral scale 24 h			
Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	963-128 KERN Balances Industiral scale 24 h 710 x 360 x 185 mm 6,670 kg			
Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	963-128 KERN Balances Industiral scale 24 h 710 x 360 x 185 mm			
Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	963-128 KERN Balances Industiral scale 24 h 710 x 360 x 185 mm 6,670 kg 5,410 kg			
Adjustment at the location of installationDAkkS Certificate:CategoryBrand:Category:Product Group:Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:Construction	963-128 KERN Balances Industiral scale 24 h 710 x 360 x 185 mm 6,670 kg 5,410 kg Parcel service			
Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device:	963-128 KERN Balances Industiral scale 24 h 710 x 360 x 185 mm 6,670 kg 5,410 kg Parcel service			
Adjustment at the location of installationDAkkS Certificate:CategoryBrand:Category:Product Group:Packaging & shippingDelivery:Dimensions packaging (WxDxH):Gross weight:Net weight:Shipping method:Construction	963-128 KERN Balances Industiral scale 24 h 710 x 360 x 185 mm 6,670 kg 5,410 kg Parcel service			
Adjustment at the location of installation DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device	963-128 KERN Balances Industiral scale 24 h 710 x 360 x 185 mm 6,670 kg 5,410 kg Parcel service			

KERN IOC10K-4

All-round platform scale with a range of communication options and EC type approval [M]



Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 240 mm

Piktogramme

STANDARD

CAL EXT RS 232	KCP PROTOCOL	GLP PRINTER	PCS	SUM	% Percent	-√+ ⊙ 🤊 TOL	MOVE
IP 65 MULTI	DMS	1 DAY	2 DAYS				

OPTION



FACTORY

