
# KERN IOC 30K-4







Measuring system	
Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	25 g   50 g
Linearisation (points):	3
Linearity:	15 g   30 g
Load cell connection:	4-wire
Readability [d]:	500 mg   1000 mg
Recommended adjusting weight:	30 kg (M1)
Repeatability:	5 g   10 g
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	2h 2h
Weighing capacity [Max]:	15 kg   30 kg
Weighing system:	Strain gauge
Weighing units:	tJ HJ PCS oz g lb kg

Display	
Display digit height (large):	2,500 cm
Display digit height (small):	2,500 cm

Technical data about verification

Minimum load [Min]:	100 g   200 g
Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	1 g
Mininum piece weight at piece counting (Normal):	10 g

Functions		
Counting function:	yes	
Percentage determination:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions		
Maximum humidity:	80 %	
Maximum operating temperature:	40 °C	
Minimum ambient temperature:	-10 °C	
Minimum humidity:	0 %	

Power supply	
Battery:	no battery
Charging time:	3 h
Input voltage:	100V-240V AC 50/60Hz 0,400 Amax
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US EURO CH UK AUS
Operating time:	100 h
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional

Services (optional)	
Adjustment at the location of installation: 961-248	
DAkkS Certificate:	963-128

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	810 x 360 x 185 mm
Gross weight:	8,600 kg
Net weight:	7,400 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	400 x 300 x 110 mm

## KERN IOC30K-4



All-round platform scale with a range of communication options and EC type approval [M]

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes Wall mount: yes

Weighing surface (WxD): 400 x 300 mm

### Piktogramme

#### STANDARD



#### **OPTION**



#### **FACTORY**

