# KERN IXS60K-3



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display



Measuring system				
Adjustment options:	External calibration			
Linearity:	6 g			
Load cell connection:	4-Leiter			
Number of weighing ranges:	1			
Readability [d]:	2 g			
Recommended adjusting weight:	60 kg (M1)			
Repeatability:	2 g			
Resolution:	30000			
Stabilisation time under laboratory conditions:	2 s			
Tare range:	-60 kg			
Warm up time:	2 h			
Weighing capacity [Max]:	60 kg			
Weighing system:	Strain gauge			
Weighing units:	kg			
Display				
Display digit height:	5,500 cm			
Counting				
Counting resolution:	30000			
Mininum piece weight at piece counting (Laboratory:	2 g			
Mininum piece weight at piece counting (Normal):	20 g			
Functions				
Counting function:	yes			
Data hold function:	yes			
Help function on the display:	yes			
Peak function:	yes			
PRE-TARE function:	yes			
Vibratian free costable a (Animal				

Vibration-free weighing (Animal

Weighing with tolerance range:	yes			
Environmental conditions	·			
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	12 h			
Input voltage:	220 V - 240 V AC 50 Hz			
Mains adapter/adapter included:	EURO			
Operating time (Backlight off):	80 h			
Operating time (Backlight on):	40 h			
Rechargeable battery:	Rchrg. battery optional (factory)			
Service				
Adjustment at the location of installation	n <sup>.</sup> 961-249			
·	1.001 240			
DAkkS Certificate:	963-129			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Industiral scale			
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	500 x 635 x 222 mm			
Gross weight:	13,050 kg			
Net weight:	10,500 kg			
Shipping method:	Parcel service			
Construction				
Cable length of display device:	2,500 m			
Dimensions of display device (WxDxH):	232 x 150 x 80 mm			
Dimensions of weighing plate (WxDxH):	400 x 300 x 89 mm			
Level indicator:	yes			
Material weighing plate:	stainless steel			
Revolving screw feet:	yes yes			
Wall mount:				
Weighing surface (WxD):	400 x 300 mm			

yes

## KERN IXS60K-3



Platform scale with stainless steel display device with IP68 rating, XL display und EC type approval [M] â now also as high resolution version with high-resolution display

### Piktogramme

#### STANDARD

CAL EXT PCS	SUM	-√+ ⊙ ⋽୬ TOL	MOVE	<b>000</b> IP 65	<b>000</b> IP 68	230 V	DMS
DAkkS +3 DAYS							

### FACTORY

	• 888. •	*		Μ	
RS 232	RS 485	BT	ACCU	+3 DAYS	